

SSUC200 series



ベアリングNo.	d		D		b		なれ		寸法		メートル		G		Ds		重量 [KG]
	で	mm	で	mm	で	mm	で	mm	で	mm	で	mm	で	mm	で	mm	
SSUC201-8	1/2		1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.19
SSUC201		12	1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.2
SSUC202-9	9/16		1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.19
SSUC202-10	5/8		1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.19
SSUC202		15	1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.19
SSUC203-11	11/16		1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.17
SSUC203		17	1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.18
SSUC204-12	3/4		1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.16
SSUC204		20	1.8504	47	1.2205	31	0.6693	17	0.5	12.7	0.7205	18.3	0.1969	5	1/4-28	M6P0.75	0.16
SSUC205-13	13/16		2.0472	52	1.3426	34.1	0.6693	17	0.563	14.3	0.7795	19.8	0.1969	5	1/4-28	M6P0.75	0.24
SSUC205-14	7/8		2.0472	52	1.3426	34.1	0.6693	17	0.563	14.3	0.7795	19.8	0.1969	5	1/4-28	M6P0.75	0.23
SSUC205-15	15/16		2.0472	52	1.3426	34.1	0.6693	17	0.563	14.3	0.7795	19.8	0.1969	5	1/4-28	M6P0.75	0.21
SSUC205-16	1		2.0472	52	1.3426	34.1	0.6693	17	0.563	14.3	0.7795	19.8	0.1969	5	1/4-28	M6P0.75	0.2
SSUC205		25	2.0472	52	1.3426	34.1	0.6693	17	0.563	14.3	0.7795	19.8	0.1969	5	1/4-28	M6P0.75	0.2
SSUC206-17	1 1/16		2.4409	62	1.5	38.1	0.748	19	0.626	15.9	0.874	22.2	0.1969	5	1/4-28	M6P0.75	0.33
SSUC206-18	1 1/8		2.4409	62	1.5	38.1	0.748	19	0.626	15.9	0.874	22.2	0.1969	5	1/4-28	M6P0.75	0.34
SSUC206-19	1 3/16		2.4409	62	1.5	38.1	0.748	19	0.626	15.9	0.874	22.2	0.1969	5	1/4-28	M6P0.75	0.32
SSUC206-20	1 1/4		2.4409	62	1.5	38.1	0.748	19	0.626	15.9	0.874	22.2	0.1969	5	1/4-28	M6P0.75	0.31
SSUC206		30	2.4409	62	1.5	38.1	0.748	19	0.626	15.9	0.874	22.2	0.1969	5	1/4-28	M6P0.75	0.32
SSUC207-20	1 1/4		2.8346	72	1.689	42.9	0.7874	20	0.689	17.5	1	25.4	0.2756	7	5/16-24	M8P1.0	0.54
SSUC207-21	1 5/16		2.8346	72	1.689	42.9	0.7874	20	0.689	17.5	1	25.4	0.2756	7	5/16-24	M8P1.0	0.51
SSUC207-22	1 3/8		2.8346	72	1.689	42.9	0.7874	20	0.689	17.5	1	25.4	0.2756	7	5/16-24	M8P1.0	0.48
SSUC207-23	1 7/16		2.8346	72	1.689	42.9	0.7874	20	0.689	17.5	1	25.4	0.2756	7	5/16-24	M8P1.0	0.45
SSUC207		35	2.8346	72	1.689	42.9	0.7874	20	0.689	17.5	1	25.4	0.2756	7	5/16-24	M8P1.0	0.48
SSUC208-24	1 1/2		3.1496	80	1.937	49.2	0.8268	21	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.68
SSUC208-25	1 9/16		3.1496	80	1.937	49.2	0.8268	21	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.65
SSUC208		40	3.1496	80	1.937	49.2	0.8268	21	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.64
SSUC209-26	1 5/8		3.3465	85	1.937	49.2	0.8661	22	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.78
SSUC209-27	1 11/16		3.3465	85	1.937	49.2	0.8661	22	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.74
SSUC209-28	1 3/4		3.3465	85	1.937	49.2	0.8661	22	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.7
SSUC209		45	3.3465	85	1.937	49.2	0.8661	22	0.748	19	1.189	30.2	0.315	8	5/16-24	M8P1.0	0.68
SSUC210-29	1 13/16		3.5433	90	2.0315	51.6	0.9449	24	0.748	19	1.2835	32.6	0.3937	10	3/8-24	M10P1.25	0.92
SSUC210-30	1 7/8		3.5433	90	2.0315	51.6	0.9449	24	0.748	19	1.2835	32.6	0.3937	10	3/8-24	M10P1.25	0.87

SSUC200 serises

SSUC210-31	1 15/16		3.5433	90	2.0315	51.6	0.9449	24	0.748	19	1.2835	32.6	0.3937	10	3/8-24	M10P1.25	0.82
SSUC210-32	2		3.5433	90	2.0315	51.6	0.9449	24	0.748	19	1.2835	32.6	0.3937	10	3/8-24	M10P1.25	0.78
SSUC210		50	3.5433	90	2.0315	51.6	0.9449	24	0.748	19	1.2835	32.6	0.3937	10	3/8-24	M10P1.25	0.8
SSUC211-32	2		3.937	100	2.19	55.6	0.9843	25	0.874	22.2	1.315	33.4	0.3937	10	3/8-24	M10P1.25	1.26
SSUC211-33	2 1/16		3.937	100	2.19	55.6	0.9843	25	0.874	22.2	1.315	33.4	0.3937	10	3/8-24	M10P1.25	1.2
SSUC211-34	2 1/8		3.937	100	2.19	55.6	0.9843	25	0.874	22.2	1.315	33.4	0.3937	10	3/8-24	M10P1.25	1.15
SSUC211-35	2 3/16		3.937	100	2.19	55.6	0.9843	25	0.874	22.2	1.315	33.4	0.3937	10	3/8-24	M10P1.25	1.09
SSUC211		55	3.937	100	2.19	55.6	0.9843	25	0.874	22.2	1.315	33.4	0.3937	10	3/8-24	M10P1.25	1.11
SSUC212-36	2 1/4		4.3307	110	2.563	65.1	1.063	27	1	25.4	1.563	39.7	0.3937	1	3/8-24	M10P1.25	1.67
SSUC212-37	2 5/16		4.3307	110	2.563	65.1	1.063	27	1	25.4	1.563	39.7	0.3937	1	3/8-24	M10P1.25	1.59
SSUC212-38	2 3/8		4.3307	110	2.563	65.1	1.063	27	1	25.4	1.563	39.7	0.3937	1	3/8-24	M10P1.25	1.52
SSUC212-39	2.4375		4.3307	110	2.563	65.1	1.063	27	1	25.4	1.563	39.7	0.3937	1	3/8-24	M10P1.25	1.45
SSUC212		60	4.3307	110	2.563	65.1	1.063	27	1	25.4	1.563	39.7	0.3937	1	3/8-24	M10P1.25	1.54